SAATI

Ecofiltra technical data

ECOFILTRA DL

Double layer cloths for liquid-solid separation

Item	Fiber	Yarn	Mesh count warp		Mesh count weft		Weight		Air permeability		Pattern	Structure	Width	Availability
	warp | weft	warp | weft	n/cm	n/inch	n/cm	n/inch	g/m²	oz/yd²	l/dm²/min 200Pa	Cfm/sq.ft-0,5"WG			cm	
PPDL 0907	PP | PP	mono | mono	62	157	28	71	420	12,4	100 - 300 - 500 - 1000	21,7 - 65,2- 108,7 - 217,4	special	woven	248	••
PPM DL 20607	PP | PP	mono | mono/multi	65	165	24	61	400	11,8	30 - 50 - 100	6,5 - 10,9 - 21,7	special	woven	248	••
PET DL 41/1000	PET | PET	mono | mono	130	330	130	330	440	13,0	n.a	n.a	PW	laminated	151-228 -210	••
PET DL75/1000	PET | PET	mono | mono	73	185	73	185	460	13,6	n.a	n.a	PW	laminated	210-228	••
PET DL 80/700	PET | PET	mono | mono	71	180	71	180	370	10,9	n.a	n.a	TW	laminated	140-210	••

The listed technical specifications, exception made for the thread diameter indicated with its nominal value, are referred to the arithmetic mean value of production samples and are subject to change, in accordance with our policy of continuously improving our products.

Polymer
PP= Polypropylene
PET= Polyester

Pattern:
PW= Plain weave
TW= Twill

Availability:
•• Routinely produced

2016.10.21