

Fixer 6

Emulsion Hardener

Applications

Increases stencil water resistance for more impressions per screen.

Characteristics

- Works as a catalyst with triple-cure emulsions
- (Ceramic HT, Textil HT, Vitrum HT) or makes a permanent, solvent-resistant and waterproof stencil
- Works as an emulsion hardener with water-resistant emulsions such as Textil DW and Textil DT to make a more durable stencil

Directions For Use

Apply SAATI Fixer 6 thinly and evenly to both sides of the dry stencil with a sponge, brush or cloth. Remove Fixer 6 excess to avoid drips with vacuum or airjet. Allow Fixer 6 to penetrate emulsion. Then cure overnight at room temperature or for one or two hours at 50° to 60°C.

Health And Safety

Before using, refer to appropriate Safety Data Sheets. Contact SAATI at info.IT@saati.com to request SDS.

Storage

When sealed in the original container and stored in cool conditions, SAATI products will maintain their original properties for one year from the date of production.

Packaging

Available in 1 and 10 kilogram containers.

Warranty And Limited Warranty

The directions, recommendations and specifications contained within this Technical Data Sheet are meant as a guide for the use of the product and shall not bind the company. Product specifications are subject to change without notice.

The following is made in lieu of all other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose; All SAATI manufactured liquid products are warranted to be free of defects in materials and manufacture and to meet the specifications in SAATI Product Bulletin.

SAATI will replace or refund the price of any SAATI manufactured liquid product that does not meet this warranty within the applicable warranty period.

The remedies are exclusive. In no case shall SAATI be liable for any other direct or indirect damage or loss, including without limitation any incidental, special or consequential damages, or any material costs or labor charges incident to the removal or replacement of any mesh, screen, ink, substrate, finished graphic or other item.