Ultrafix SB12 Plus

2-Part Frame Adhesive

Applications

SAATI Ultrafix SB12 Plus is used for bonding mesh onto stretch & glue screen printing frames.

Characteristics

- Two-component polyurethane adhesive
- Red color with low viscosity for use with medium to fine mesh counts
- Adheres screen mesh to onto aluminum, steel, iron, plastic-coated, and wooden frames

Features/Benefits

- Fast drying and curing time for maximum initial adhesion - allows screens to be removed quickly from stretching system and saves time in stretching
- Maximum flexibility & adhesion - prevents premature failure and enables maximum screen life
- Excellent resistance to heat & solvents - for repeated use in automated screen reclaiming systems

Directions For Use

Mix 5 parts of Ultrafix SB12 Plus adhesive with 1 part of Catalyst by weight. Use within 45 to 60 minutes. To obtain optimal adhesion, degrease the frame. Stretch the fabric over the frame providing good contact between the two. Apply the prepared mixture with a brush. After the adhesive has dried and cured, release tension and remove the screen from the stretching system. To achieve maximum heat and solvent resistance, allow adhesive to cure for 24 hours before use.

Health And Safety

Before using, refer to appropriate Safety Data Sheets. Contact SAATI at info.IT@saati.com to request SDS.

Storage

When sealed in the original container and stored in cool conditions, this SAATI chemical product maintains original properties for one year from the date of production. Keep away from sources of direct light and heat, and prevent from freezing.

Packaging

Ultrafix SB4 Plus is available in 0.90 or 4.5 kg containers, and Catalyst SB4 Plus is available in 0.18 or 0.9 kg containers.

Warranty And Limited Warranty

The directions, recommendations and specifications contained within this Technical Data Sheet are meant as a guide for the use of the product and shall not bind the company. Product specifications are subject to change without notice.

The following is made in lieu of all other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose; All SAATI manufactured liquid products are warranted to be free of defects in materials and manufacture and to meet hte specifications in SAATI Product Bulletin.

SAATI will replace or refund the price of any SAATI manufactured liquid product that does not meet this warranty within the applicable warranty period.

The remedies are exclusive. In no case shall SAATI be liable for any other direct or indirect damage or loss, including without limitation any incidental, special or consequential damages, or any material costs or labor charges incident to the removal or replacement of any mesh, screen, ink, substrate, finished graphic or other item.

SAATI S.p.A.
Via Milano, 14-22070
Appiano Gentile (CO), Italy

www.saati.com

HQ +39 03 97 11
Fax +39 031 933 392
info.it@saati.com

US +1 800 4312200
Fax +1 864 8620089
info.us@saati.com

CN +86 22 23960843
Fax +86 22 23962116
info.cn@saati.cn