

Positector 6000

Electronic Thickness Gauge – Measure Stencil Thickness vs Mesh Thickness to Determine Stencil Thickness – EOM

Simplicity

- Fast measurement speed—60+ readings per minute. Enhanced FAST mode — 90+ readings per minute for quick inspection.
- Ready to measure—no adjustment required for most applications
- NEW Larger 2.8" / 7 cm impact resistant color touchscreen with redesigned keypad
- for quick menu navigation
- NEW On-gauge help explains menu items at the touch of a button
- Flashing display—ideal in a noisy environment
- RESET feature instantly restores factory settings

Durability

- NEW Weatherproof, dustproof, and water-resistant IP65-rated enclosure
- NEW Ergonomic design with durable rubberized grip
- Wear-resistant probe tip
- Shock-absorbing protective rubber holster for added impact resistance
- Two year warranty on gage body AND probe

Accuracy

- Certificate of Calibration showing traceability to NIST or PTB included
- Built-in temperature compensation ensures measurement accuracy
- Hi-RES mode increases displayed resolution for precision applications
- Conforms to national and international standards including ISO and ASTM

All Gages Come Complete

With precision plastic shim(s), protective rubber holster, wrist strap, 3 AAA alkaline batteries, instructions, protective lens shield, convenient carrying case, Long Form Certificate of Calibration traceable to NIST or PTB, USB cable, PosiSoft Software, two (2) year warranty.

- Size: 127 x 66 x 25.4 mm (5" x 2.6" x 1")
- Weight: 137 g (4.9 oz.) without batteries
- Size and weight are for the PosiTector gage body only and do not include the probe.
- Conforms to ISO 19840/2178/2360/2808, ASTM B244/B499/D1186/ D1400/D7091/E376/ G12, BS3900-C5, SSPC-PA2 and others

