

Technical data sheet

REMOVE PW 30

APPLICATIONS

Removes ink from mesh after and before screen printing.

GENERAL CHARACTERISTICS

Solvent mixture characterized by medium evaporation, designed for cleaning and removing UV and solvent based inks in graphic printing.

May be used successfully even in automatic cleaning machines.

DIRECTIONS FOR USE

To optimize the cleaning process we recommend to use cotton rag ; avoid synthetic material. Alternatively, we suggest to use highly absorbent paper.

Cleaning during printing process

Apply some spray of Remove PW30 on the rag and start to clear the printing area ; repeat the process two time, folding the cloth every time. After this treatment the area is still full of ink; make some blank printing and restart the process interrupted.

Final cleaning

Place the screen on a flat surface, where it was spread absorbent material (sheets of paper). Using a handy spray bottle, apply some spray of Remove PW30 remover on the ink surface and mix it with the help of a plastic brush.

Place a rag along the shorter side of screen and use a squeegee to collect the mixture Remove/ink from the opposite side of the cloth; collect into the rag the material removed.

Recycle most of removed material with the help of the cloth; clean both sides and corners of screen. Remove the screen from the support and end the cleaning step applying some sprays of Remove PW30 on both sides working with a cotton rag.

Following this procedure and using Remove PW30, we obtain these improvements:

- Minimum quantity of solvent used for cleaning
- Minimum use of cleaning material (rags)

HEALTH AND SAFETY

Before using, refer to appropriate safety data sheets.

STORAGE

When sealed in the original container and stored at temperature between 20 and 25°C, REMOVE PW30 will maintain original properties for 36 months from the date of production.

PACKAGING

REMOVE PW30 is available in 1, 5, 30 and 200 kilogram containers.

WARRANTY AND LIMITED REMEDY

The directions, recommendations and specifications contained in this Technical Data Sheet are meant as a guide to the use of the product and shall not bind the company. Product specifications are subject to change without notice.

The following is made in lieu of all other expressed or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose: all Saatichem manufactured liquid products are warranted to be free of defects in materials and manufacture and to meet the specifications stated in Saatichem applicable Product Bulletin. Saatichem will replace or refund the price of any Saatichem manufactured liquid product that does not meet this warranty within the applicable warranty period.

The remedies are exclusive. In no case shall Saatichem be liable for any other direct or indirect damage or loss, including without limitation any incidental, special or consequential damages, or any material costs or labor charges incident to the removal or replacement of any mesh, screen, ink, substrate, finished graphic or any other item.

SAATI S.p.A. | P: (+39) 031 9711 | F: (+39) 031 933392 | E: info.IT@saati.com | www.saati.com

To receive the Material Safety Data Sheet (MSDS), please send an e-mail to: MSDS@saatichem.com
To get more information or contact us visit our Web Site: www.saati.com