

Technical data sheet

ULTRAFIX CA series

APPLICATIONS

Frame adhesive.

GENERAL CHARACTERISTICS

- Spray-activated cyanoacrylate adhesive
- Mounts screen mesh onto aluminium, steel, iron, plastic-coated and wood frames
- Cure instantly
- Highly resistant to water and solvents
- Standard cyanoacrylate available in three viscosities – Ultrafix CA50, CA100 and CA150
- Ultrafix C-Flex is a toughened, more flexible version

DIRECTIONS FOR USE

To obtain optimal adhesion, degrease the frame. Stretch the fabric over the frame providing good contact between the two. Squeeze a thin bead of adhesive onto fabric around the frame perimeter and spread evenly. Lightly spray the applied adhesive with Ultrafix CA Activator which sets in less than 30 seconds. Release tension and remove the screen from the stretching system.

HEALTH AND SAFETY

Before using, refer to appropriate material safety data sheets.

STORAGE

When sealed in the original container and stored and at a temperature below 22°C (71°F), ULTRAFIX CA Series will maintain original properties for 24 months from the date of production.

In case of long-term storage, we recommend to maintain well sealed containers in a refrigerated place.

WARNING!

To prevent premature curing, we suggest to close carefully containers after any use.

PACKAGING

ULTRAFIX CA are available in 50 and 450 gr. containers.

ULTRAFIX CA Activator A is available in 160 gr. containers.

WARRANTY AND LIMITED REMEDY

The directions, recommendations and specifications contained in this Technical Data Sheet are meant as a guide to the use of the product and shall not bind the company. Product specifications are subject to change without notice.

The following is made in lieu of all other expressed or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose: all Saatichem manufactured liquid products are warranted to be free of defects in materials and manufacture and to meet the specifications stated in Saatichem applicable Product Bulletin. Saatichem will replace or refund the price of any Saatichem manufactured liquid product that does not meet this warranty within the applicable warranty period.

The remedies are exclusive. In no case shall Saatichem be liable for any other direct or indirect damage or loss, including without limitation any incidental, special or consequential damages, or any material costs or labor charges incident to the removal or replacement of any mesh, screen, ink, substrate, finished graphic or any other item.

SAATI S.p.A. | P: (+39) 031 9711 | F: (+39) 031 933392 | E: info.IT@saati.com | www.saati.com

To receive the Material Safety Data Sheet (MSDS), please send an e-mail to: MSDS@saatichem.com
To get more information or contact us visit our Web Site: www.saati.com