

Technical data sheet

ULTRAFIX PT Plus

APPLICATIONS

Adhesive for pallet for T-shirt printing.

GENERAL CHARACTERISTICS

- Water-based pressure-sensitive adhesive
- Fast in drying
- Flash safe and non-staining
- Non-flammable and no VOC's

DIRECTIONS FOR USE

Apply directly onto pallet or on top of pallet protecting tape. Spread a thin layer with brush, roller, card or squeegee and allow to dry before use. Can also be spray-applied using pneumatic or electric-operated spray gun. Can be reapplied, or tack can be reactivated by wiping with sponge and warm water to remove lint build-up. Remove old adhesive by cleaning with Remove PW7 ink degrader, or other suitable solvent.

HEALTH AND SAFETY

Before using, refer to appropriate material safety data sheets.

STORAGE

When sealed in the original container and stored at temperature between 20 and 25°C, ULTRAFIX PT Plus will maintain original properties for 24 months from the date of production.

WARNING :
Protect from frost

PACKAGING

ULTRAFIX PT Plus are available in 1, 5 and 200 kilogram containers.

WARRANTY AND LIMITED REMEDY

The directions, recommendations and specifications contained in this Technical Data Sheet are meant as a guide to the use of the product and shall not bind the company. Product specifications are subject to change without notice.

The following is made in lieu of all other expressed or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose: all Saatichem manufactured liquid products are warranted to be free of defects in materials and manufacture and to meet the specifications stated in Saatichem applicable Product Bulletin. Saatichem will replace or refund the price of any Saatichem manufactured liquid product that does not meet this warranty within the applicable warranty period.

The remedies are exclusive. In no case shall Saatichem be liable for any other direct or indirect damage or loss, including without limitation any incidental, special or consequential damages, or any material costs or labor charges incident to the removal or replacement of any mesh, screen, ink, substrate, finished graphic or any other item.

SAATI S.p.A. | P: (+39) 031 9711 | F: (+39) 031 933392 | E: info.IT@saati.com | www.saati.com

To receive the Material Safety Data Sheet (MSDS), please send an e-mail to: MSDS@saatichem.com
To get more information or contact us visit our Web Site: www.saati.com