

# Technical data sheet

# ULTRAFIX remover

## APPLICATIONS

Removes frame adhesives.

## GENERAL CHARACTERISTICS

- Remove Ultrafix adhesive residue from screen printing frames and other hard surfaces
- Effective and fast-acting adhesive

## DIRECTIONS FOR USE

Stir Ultrafix Remover before use. Using a paintbrush, generously apply Ultrafix Remover Gel to the glue-covered surface. Allow it to stand for a minimum of one hour and longer for thicker coats of glue. Using a scraper, such as a paint scraper, remove adhesive. Carefully rinse off excess before using a pressure washer to remove any remaining of Ultrafix Remover. Repeat if necessary.

## HEALTH AND SAFETY

Before using, refer to appropriate material safety data sheets.

## STORAGE

When sealed in the original container and stored at temperature between 20 and 25°C, ULTRAFIX REMOVER will maintain original properties for 24 months from the date of production.

## PACKAGING

ULTRAFIX REMOVER is available in 1 and 5 kilogram containers.

### WARRANTY AND LIMITED REMEDY

The directions, recommendations and specifications contained in this Technical Data Sheet are meant as a guide to the use of the product and shall not bind the company. Product specifications are subject to change without notice.

The following is made in lieu of all other expressed or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose: all Saatichem manufactured liquid products are warranted to be free of defects in materials and manufacture and to meet the specifications stated in Saatichem applicable Product Bulletin. Saatichem will replace or refund the price of any Saatichem manufactured liquid product that does not meet this warranty within the applicable warranty period.

The remedies are exclusive. In no case shall Saatichem be liable for any other direct or indirect damage or loss, including without limitation any incidental, special or consequential damages, or any material costs or labor charges incident to the removal or replacement of any mesh, screen, ink, substrate, finished graphic or any other item.

SAATI S.p.A. | P: (+39) 031 9711 | F: (+39) 031 933392 | E: [info.IT@saati.com](mailto:info.IT@saati.com) | [www.saati.com](http://www.saati.com)

To receive the Material Safety Data Sheet (MSDS), please send an e-mail to: [MSDS@saatichem.com](mailto:MSDS@saatichem.com)  
To get more information or contact us visit our Web Site: [www.saati.com](http://www.saati.com)