



## Technical data sheet

# **SAATIBELT PES 8.400-9.400**

# Belting Solution for Pasta Drying





SAATIBELT® PES 8.400

SAATIBELT® PES 9.400

### **Key-Features:**

- · High tensile strenght
- · Excellent dimension stability
- Smooth surface
- Hydrolisis resistance
- Excellent protection from moisture
- FDA polymer approved
- Washable
- Edge and joint customization

### Application areas:





TECHNICAL DATA		
PRODUCT NAME	Saatibelt® PES 8.400	Saatibelt® PES 9.400
WARP / WEFT COMPOSITION	Monofilament Polyester	Monofilament Polyester
MESH OPENING	870 μm	710 μm
OPEN AREA	47 %	41%
THREAD DIAMETER	403 μm	405 μm
WEIGHT	290 [g/m²]	320 [g/m²]
THICKNESS	745 μm	735 µm
AVAILABLE WIDTHS	2500 up to mm	2500 up to mm
MAX. WORKING TEMPERATURE	140 [°C]	140 [°C]

The listed technical specifications are referred to mean values of production samples.

In accordance with our policy of continuosly improving our products, the above technical specifications are subject to change without any notice.

PES (PET)= Polyester

#### **Company Profile**

SAATI is a leader in the production and distribution of dryer, conveyor and filter belts used in many applications. The SAATIBELT® line of products is manufactured from technically advanced fibers that offer the highest resistance, reliability and durability. SAATIBELT® conveyors are fabricated to customer's exact specifications in UNI EN ISO 9001 certificated facilities.