

Cam Spray Electric Pressure Washers

Cart Mounted Models

Compact yet powerful industrial strength pressure washers that deliver 1000, 2000 or 2300 pounds per square inch of water pressure. They are easy to use and store. These units have power cords with GFI, ground fault interruptors for added protection.

These pressure washers have **auto start/stop**, adjustable pressure, trigger gun and two piece adjustable 0 to 60 spray tip and easy to use quick connectors on the hose. Ceramic pump plungers with replaceable stainless steel valves, forged crankshaft, roller bearings in oil bath lubrication.

Features

- Triplex plunger pump with ceramic plungers and stainless steel valves
- Auto start-stop mounts to the wall near the pressure washer
- Ground fault interruptor
- Adjustable pressure
- Non-marking hose
- Trigger gun
- 36" two-piece wand
- Multi-reg 0 to 60 degree pattern tip with Hi-Low for chemical injection

Warranty

One year warranty.



1000XS Specifications	
PSI/Bar	1000/69
GPM/LPM	2.2/8.4
Horsepower	1.5
Voltage/Amp/Phase	120V/15A/1
Pump Max Temperature	140°F
Thermal	Mechanical
Dimensions	30"L x 21.5"W x 36"H
Ship Weight	150 lbs
Power Cord	35'

2000XAR Specifications	
PSI/Bar	2000/138
GPM/LPM	4.0/15.2
Horsepower	5
Voltage/Amp/Phase	230V/26A/1
Pump Max Temperature	160°F
Thermal	Mechanical
Dimensions	37"L x 23.5"W x 36"H
Ship Weight	215 lbs
Power Cord	35'

2305X Specifications	
PSI/Bar	2300/159
GPM/LPM	5.0/18.9
Horsepower	7.5
Voltage/Amp/Phase	208V/26A/1
Pump Max Temperature	140°F
Thermal	Mechanical
Dimensions	37"L x 23.5"W x 36"H
Ship Weight	265 lbs
Power Cord	10'

Cam Spray Electric Pressure Washers

Base Mounted Models

The Base Mounted Cam Spray cold water industrial electric pressure washer is a bare bones motor and pump combination that is designed to be mounted to a flat surface using the foot mount base of the electric motor. 1000, 2000 & 2300 PSI models features include **auto start-stop**, industrial motors that are totally enclosed and thermal overload protected, industrial triplex plunger pump with ceramic plungers and stainless-steel valves are protected by unloader valves. 0°, 15°, 25° and 40° Q-meg tips and trigger gun are included.

Features

- Triplex plunger pump with ceramic plungers and stainless steel valves
- Auto start-stop function attaches to handle
- Adjustable pressure
- Multi-reg 0 to 40 degree pattern tip with Hi-Low for chemical injection

Warranty

One year warranty.



1000GEAR Specifications	
PSI/Bar	1000/69
GPM/LPM	2.2/8.4
Horsepower	1.5
Voltage/Amp/Phase	120V/15A/1
Pump Max Temperature	140°F
Thermal	Mechanical
Dimensions	28"L x 20"W x 13"H
Ship Weight	150 lbs
Power Cord Length	35' with GFCI

2000GEAR Specifications	
PSI/Bar	2000/138
GPM/LPM	4.0/15.2
Horsepower	5
Voltage/Amp/Phase	230V/26A/1
Pump Max Temperature	140°F
Thermal	Mechanical
Dimensions	28"L x 20"W x 13"H
Ship Weight	150 lbs
Power Cord	10'

2305GEAR Specifications	
PSI/Bar	2300/159
GPM/LPM	5.0/18.9
Horsepower	7.5
Voltage/Amp/Phase	230V/34A/1
Pump Max Temperature	160°F
Thermal	Mechanical
Dimensions	28"L x 20"W x 13"H
Ship Weight	150 lbs
Power Cord	10'

Cam Spray Electric Pressure Washers

Wall Mounted Models

Cam Spray wall mount pressure washers keep the pressure washing equipment safe and secure, mounted to the wall. Frame design includes a hook to hang the gun, hose and wand below the pressure washer.

The frame features an industrial coating and grommets to hold the nozzles.

Features include **auto start-stop**, an industrial motor that is totally enclosed and thermal overload protected, industrial triplex plunger pump with ceramic plungers and stainless steel valves is protected by unloader valve.

0°, 15°, 25° and 40° Q-meg tips and trigger gun included. 1500WM/SS is a deluxe model boasting greater protection for tougher environments.

Features

- Triplex plunger pump with ceramic plungers and stainless steel valves
- 1500 & 2040EWMA have wall mount Auto Start-Stop, 1500WM/SS has an Auto start-stop feature built-in
- Adjustable pressure
- Multi-reg 0 to 40 degree pattern tip with Hi-Low for chemical injection

Warranty

One year warranty.



1500EWM2A Specifications	
PSI/Bar	1450/103.5
GPM/LPM	2.2/8.4
Horsepower	2
Voltage/Amp/Phase	120V/20A/1
Pump Max Temperature	160°F
Thermal	Mechanical
Dimensions	23"L x 16"W x 31"H
Ship Weight	170 lbs
Power Cord	35', with GFCI

2040EWMA Specifications	
PSI/Bar	2000/138
GPM/LPM	4.0/15.2
Horsepower	5
Voltage/Amp/Phase	230V/26A/1
Pump Max Temperature	160°F
Thermal	Mechanical
Dimensions	28"L x 22"W x 30"H
Ship Weight	220 lbs
Power Cord	10'

1500WM/SS Specifications	
PSI/Bar	1500/103.5
GPM/LPM	3.0/11.4
Horsepower	3
Voltage/Amp/Phase	230V/20A/1
Pump Max Temperature	160°F
Thermal	Mechanical
Dimensions	23"L x 16"W x 31"H
Ship Weight	210 lbs
Power Cord	35', with GFCI