

Technical data sheet

DURALIFE CE SQUEEGEE

Duralife Cut Edge squeeges are engineered to have great production performance in order to meet specific demands of the global screen printing industry.

Thanks to our exclusive polyurethane formulation, Duralife CE squeegee are resistant to both chemicals and abrasion making them suitable for all applications.

CHARACTERISTICS

Hardness (SH): from 50 Shore to 90 Shore

Standard length: 3660 mm
Width: from 20 mm to 100 mm
Thickness: from 4 mm to 10 mm

FEATURES

- · Extremely solvent resistant with low swelling
- UV ink resistant
- · Good abrasion resistance
- · Not affected by humidity
- Good re-sharpening
- · Resists nicking
- Great all around performance

Duralife CE Squeegee Color Coding System		
50 durometer	Transparent	
60 durometer	Orange	
65 durometer	Yellow	
70 durometer	Blue	
75 durometer	White	
80 durometer	Red	
85 durometer	Pink	
90 durometer	Gray	





Technical data sheet

DURALIFE CE SQUEEGEE


TRIPLE RANGE:


Single Bevel

Single Bevel Flat Edge

Duralife CE Triple is a line of squeeges made out of three layers: two exterior layers softer and a rigid inner core. This ensures firstclass print results, especially in high-end graphic industry.

Duralife CE Squeegee Triple Durometer Models				
60/90/60				
65/90/65				
65/90/75 Modular				
70/90/70				
75/90/75				
80/90/80				
85/90/85				







Triple Duro

SQUEEGEE PROFILES 80 SH 85 SH 90 SH UV/Industrial

